

Flume Sconce Installation Instructions

Important: Installation must be performed by a **licensed electrician**.

Read these instructions thoroughly before starting.

This fixture must be installed in accordance with all applicable codes by a qualified person familiar with low-voltage systems, lighting equipment, and associated hazards.

Large Approx 12 lbs / Small Approx 9 lbs

Safety Precautions

- **Turn off power** at the circuit breaker before starting any electrical work.
 - This is a **low-voltage 24V fixture**. Use **only** the included 24V **driver/dimmer wall switch**.
 - Ensure all wiring connections are secure and properly grounded.
 - Follow all local and national electrical codes during installation.
-

Installation Steps

1. Install the Included 24V Driver/Dimmer Wall Switch

- Mount the driver/dimmer switch in a standard wall box.
- Follow the provided wiring diagram for correct low-voltage installation.
- Ensure proper ventilation for the driver if recessed into the wall.

2. Prepare the Wall Sconce Mounting

- Remove the **mounting bracket bar** from the back of the sconce canopy.
- Attach the bracket bar securely to the **junction box (J-box)** in the wall using appropriate fasteners.

3. Make Electrical Connections

- Connect the **low-voltage wires** from the fixture to the driver/dimmer circuit.
- Ensure polarity is correct: match positive (+) and negative (–) terminals.
- Double-check that all connections are tight and in compliance with low-voltage installation standards.

4. **Attach the Canopy**

- Carefully position the sconce canopy over the mounting bracket bar.
- Secure the canopy to the bracket using the provided screws or fasteners.

5. **Adjust for Plumb**


- Check the fixture for vertical alignment.
- Make any necessary adjustments to ensure the sconce is mounted **plumb** (perfectly vertical).

Need Help?

If you have questions about installation, please contact:

Lamps by Hilliard

 info@hilliardlamps.com

 707.826.1545 (Pacific Time)