

## Sophia Chandelier Installation Instructions

**Important:** Installation must be performed by a **licensed electrician**.

Read these instructions thoroughly before starting.

This fixture must be installed in accordance with all applicable codes by a qualified person familiar with low-voltage systems, lighting equipment, and associated hazards.

---

1 Pendant Approx 18 lbs / 3 Pendants Approx 55 lbs / 4 Pendants Approx 75 lbs

Two people are recommended for safe handling and installation.

---

### Safety Precautions

- **Turn off power** at the circuit breaker before beginning any electrical work.
  - Use appropriate lifting techniques or equipment to support the fixture during installation.
  - Do **not** use a knife or sharp object to remove protective wrapping — this may damage the finish or wiring.
  - Follow all local building and electrical codes.
  - Ensure all connections are secure and properly grounded.
- 

### Installation Overview

#### 1. Unpack Components Carefully

- Remove the outer wrapping from the canopy **without using a knife**.
- Leave pendants wrapped until fully installed to prevent damage.
- Place a **thick towel or foam pad** (from shipping materials) under the pendant to protect it during installation.

#### 2. Determine Fixture Orientation

- Identify the correct orientation of the pendant **based on room layout**.
- Make sure the holes in the **steel mounting bracket** align with your planned pendant direction.

### 3. Mount the Canopy

- Secure the steel canopy bracket to the ceiling according to applicable codes.
- Use hardware appropriate for the ceiling structure and weight of the fixture.

### 4. Attach Hanging Rods to Pendant

- Starting with the **shortest pendant**, fish the fixture wire **up through the hanging rod**.
- Thread the rod onto the **all-thread nipple** at the top of the stirrup (on the pendant).
- Ensure the rod is tight and the pendant is secure.

### 5. Wire and Secure Pendants

- Pass the pendant wire through the **appropriate hole in the canopy**.
- Inside the canopy, secure the pendant using the **lock washer** and **large brass knurled nut**.
- Route the wire to the **center of the canopy** for electrical connection.

### 6. Repeat for Remaining Pendants

- Continue with pendants from **shortest to longest** to ensure proper spacing and aesthetics.
- Connect all pendant wires to the main electrical connection inside the canopy. **Double-check connections and grounding.**

### 7. Final Assembly


- Carefully remove protective foam wrap from each pendant. **Do not use a knife.**
- Place the **magnet on the crossbar** and attach the **inspection cap** to complete the installation.

---

## Need Help?

If you have any questions or need support during installation, contact us:

**Lamps by Hilliard**

 707.826.1545

 [info@hilliardlamps.com](mailto:info@hilliardlamps.com)

# HILLIARD

## CEILING CANOPY INSTALLATION

all parts below included

